



2746

Thermal, On-demand Metal Bar Code Printer

Metal printers fit your industrial applications and your budget.

Sturdy metal construction, coupled with high quality features such as dual processors, flash-based architecture, standard rewind, and peel capability, make the 2746 an ideal choice for industrial labeling requirements.

Stretch Your Dollar

For a printer that handles a variety of label lengths and widths and prints up to six inches per second, the 2746 is extremely affordable. This tough, hardworking printer also supports a range of options including LAN/Ethernet adapter, real time clock, memory upgrades, keyboard display unit, and cutter.



2746

Tough, Hardworking Printer

- Sturdy, steel enclosure
- Dual processors
- Flash architecture for storage of fonts, formats and graphics and quick, easy firmware upgrades
- 512KB Flash; 256KB SRAM
- Standard rewind and peel
- Selectable print speeds up to six inches per second
- 203dpi print resolution

Variety of Options

- Real time clock
- Up to 1MB Flash; 512KB SRAM
- Ethernet connectivity
- Keyboard display unit for stand-alone printing
- Cutter

For more information

Contact your Zebra representative for additional printer specifications. For information on Zebra's full-size and mobile printers, supplies, software, and accessories, ask your reseller, call +1 800.423.0442 or visit our Web site.

www.zebra.com



Zebra Bar Code Products

International Headquarters

333 Corporate Woods Parkway
Vernon Hills, IL 60061-3109 U.S.A.
Phone: +1 847.634.6700 or +1 800.423.0442
Fax: +1 847.913.8766
www.zebra.com

Other Locations

United States: California, Florida, Rhode Island, Wisconsin
Europe: France, Germany, Italy, United Kingdom
Asia: Hong Kong, Japan, Seoul, Singapore



FM-32328
An ISO 9001 registered company

©2001 Zebra Technologies Corporation
Printed in U.S.A.



#11164L Rev. 2 (4/01) 5M



Connect with it. Count on it.™

Specifications at a Glance*

Standard Features

- Print methods: Direct thermal and thermal transfer
- Construction: Steel enclosure
- 512KB Flash memory; 256KB SRAM
- Dual processors
- Rewind and peel
- Label present sensor for peel mode
- Selectable print speeds: 2"/151mm, 4"/102mm, or 6"/152mm per second
- Media sensor for black marks, see through, die-cut labels and label out
- Rear feed slot for fanfold or oversized roll labelstock
- Diagnostics and configuration print-out and ASCII dump
- Windows® drivers (95, 3.xx, NT v.3.51, NT v.4.0)
- Windows printer utilities

Programming

- ASCII EPL2 programming language (Page Mode)
- Text and bar codes printed in 0°, 90°, 180°, 270°
- Variable field support (up to 100)
- Counter support (up to 10)
- Variable field addition and subtraction
- Status reporting
- Form storage

Operating Characteristics

Environment

- Operating Temp. 32°F/0°C to 105°F/40°C
- Storage/Transport Environ. -40°F/-40°C to 140°F/60°C
- Operating Humidity 10-90% non-condensing
- Ventilation Free air

Electrical

- Input: 120VAC; 60Hz or 240VAC; 50Hz

Communication Interface Capabilities

- Serial RS232 (DB9)
- 4.8-38.4K bits/second
- Flow control: Xon/Xoff or DTR/DSR, hardware selectable
- Parallel (Centronics)
- LAN/Ethernet (requires optional ZebraNet® PrintServer II)

Agency Approvals

- FCC Class A and CE requirements: built to UL, CUL requirements

Media Characteristics

Labels

- Max. Roll Size
- 8"/203mm O.D. on a 3"/76mm I.D. core
- Thickness (label & liner)
- .003"/.08mm to .0075"/.18mm
- Media Types
- Roll-feed, die-cut, continuous, fanfold; tags; tickets

For optimum print quality and print engine performance, use Genuine Zebra supplies.

Ribbons

- Max. Roll Size
- 2.8"/71mm O.D. on a 1"/25.4mm I.D. core
- Standard Length
- 14,270"/362m capacity
- Ribbon Set-up
- Ribbon wound ink side out

Ribbon is recommended to be at least as wide as media.

Fonts/Graphics/Symbologies

Fonts and Character Sets

- Standard Fonts: 5 bitmapped, expandable 8x
- Sets: International character sets supporting the following code pages:
 - DOS: 437, 737, 850, 851, 855, 857, 860, 861, 862, 863, 865, 866, 869
 - Windows: 1250, 1251, 1252, 1253, 1254, 1255, 1256, 1257
- Asian language support (optional)
- Soft font storage in Flash memory

Graphic Features

- Line and box drawing
- PCX graphic storage

Bar Code Symbologies

- Linear Bar Codes: Code 39, Code 128 (A, B or C user selectable/Auto select), UCC/EAN-128, Code 93, Codabar, Interleaved 2 of 5, UPC-A, UPC-E, UPC-A with 2 and 5 add on, Plessey, POSTNET, German Post,
- 2-Dimensional: PDF-417, Maxi Code (Modes 2, 3, 4, 6)

Options and Accessories

- ZebraNet PrintServer II (for Ethernet connectivity)
- Expanded memory (up to 1MB Flash; 512KB SRAM)
- Keyboard display unit (KDU)
- Cutter
- Asian language support
- RS422 serial interface
- Real time clock
- Asian language support
- Windows label design software

*Specifications listed are for base model printers with standard features only unless otherwise noted. Specifications subject to change without notice. All product and brand names are trademarks of their respective companies. All rights reserved.



2 7 4 6

The 2746 is ideal for medium-volume printing applications including:

- Shipping/Receiving
- UPC and EAN product marking
- Logistics and inventory control
- Manufacturing and compliance labeling

Genuine Zebra Supplies

Zebra-brand supplies are made for your Zebra printer! Protect your printer investment and maximize your printer performance by choosing from Zebra's 1,000+ combinations of labels, ribbons, and tags—more than 300 of which are UL-recognized and CSA-accepted. Our Zip Ship stocking program has hundreds of ribbons and labels readily available—including synthetic labels. And if you're not sure what you need, you can try before you buy through Zebra's sample program. Our media specialists are ready to help you find the right media combination for your application!

Add-on Features

With Zebra's wide range of options and accessories—including Ethernet connectivity, KDU (keyboard display unit), and label design software—you can tailor your printer's capabilities for your specific application needs. For more details, see Options and Accessories under Specifications at a Glance.

2746

Maximum Print Area

Width: 4.09"/104mm

Length:

11"/279mm (with standard memory)

22"/558mm (with optional memory)

Resolution

203dpi/8dots per mm

Maximum Print Speed

6"/152mm per second

Memory

Standard: 512KB Flash; 256KB SRAM

Optional: up to 1MB Flash; 512KB SRAM

Physical Characteristics

Width: 9.5"/241mm

Depth: 16.75"/425mm

Height: 12.38"/314mm

Weight: 26.6lbs./11.9kg

Media Specifications

Label and liner width:

.003"/.0762mm to .0075"/.19mm

Ribbon width:

1.3"/33mm to 4.3"/110mm

Distribuito da:

RCE S.r.l.

Via Salvatore Calenda, 6A

84126 SALERNO

Tel. 089 252625

Fax 178 2726634

www.rce.it

e-mail vendite@rce.it